

METAL CABLE CO.

DATA SHEET

No : MC – 22943

Date : 95.05.11

Low voltage power cable

Acc. IEC 60502-1 (or ISIRI 3569-1) , (0.6/1)1.2 kv , frequency : 50Hz

Copper conductor/ XLPE insulated/ PVC bedding/ galvanized steel wire armour/ PVC outer sheath
CU/XLPE/BD/GSWA/PVC (N2XRY-O)

R	SPECIFICATION		
1	Cable size		3x120 mm ²
2	Conductor	material	Plain annealed stranded copper
		Class	2 , sector
		construction	37x2.08 mm
3	Insulation	material	XLPE
		operation temp.	90°C
		thickness	1.2 mm
		colour	Blue , Red , Yellow
4	Bedding	material	PVC
		operation temp.	90°C
		thickness	1.2 mm
		colour	Black
5	Armour	material	Galvanized steel
		type	Wire Armour (GSWA)
		diameter	2.0 mm
6	Outer jacket	material	PVC
		operation temp.	90°C
		thickness	2.3 mm
		colour	Black
7	Overall diameter approx.		41.0 mm
8	Max. dc conductor resistance at 20°C		0.153 Ω/km acc. IEC 60228
9	Max. ac conductor resistance at 20°C		0.196 Ω/km
10	Min. Insulation resistance at 90 °C		0.250 MΩ . km
11	Short circuit current		17.14 kA at 1 second
12	High voltage test		3.5 kvac or 8.4 kvdc for 5 min
13	Working temperature		-25 ___ +90 °c
14	Min. bending radius		6 x D (Overall diameter)
15	Flame retardant test		Acc. IEC 60332-1
16	Max cable length (per drum)		1000 M
17	Cable weight approx.		5350 kg/km

Marking : METAL CABLE CO. IEC 60502-1 N2XRY-O 3x120 SQMM 0.6/1 kv MADE IN IRAN 1395 length

Technical approval